

- 5. VSWR NOT TO EXCEED 1.25:1 THRU 18 GHz
- 4. ADAPTOR TO MEET OR EXCEED ALL SPECIFICATIONS PER MIL-39012
- 3 FINISH.


BODY AND COUPLING NUT: PASSIVATE PER QQ-P-35 CONTACT: GOLD PER MIL-G-45204: TYPE II. CLASS 2, OVER COPPER PER MIL-C-14550, CLASS 4

2. MATERIAL:

BODY: STAINLESS STL PER MIL-T-8504 TYPE 303 COUPLING NUT STAINLESS STL PER QQ-S-764 TYPE 303 CONTACT: BERYL. COPPER PER QQ-C-530 INSULATOR: TEFLON PER MIL-P-19468A

1. MATING DIMS IN ACCORDANCE WITH MIL-STD-348

## NOTES:



## NOTICE

This drawing embodies a CONFIDENTIAL proprietary design originated by United Microwave Products, Inc., and all design, manufacturing, reproduction, use and sale rights regarding the same are expressly reserved. It is submitted under a confidential relationship for a specified purpose and the recipient agrees by accepting this drawing not to supply or disclose any information regarding it to any unauthorized person or to incorporate in other projects any special feature peculiar to this design. All patent rights hereto are expressly reserved by United Microwave Products Inc.

WEIGHT SCALE NONE N/A

## TOLERANCES AND NOTES EXCEPT AS NOTED DIMENSIONS ARE IN INCHES

LINEAR XX ± .015 ANGULAR ± 1/2 ° FRACTION ± 1/32 XXX ± .005

- 1. MACHINE FINISH 63 RMS
- 2 . BREAK ALL SHARP EDGES .002
- 3. ALL MACHINED FILLLETS 4. ALL MACHINED SURFACESS SQUARE TO
- RESPETIVE AXIS WITHIN .003 PER INCH.
- 5. MACHINED DIAMETERS TO BE .
- CONCENTRIC WITHIN .002 .003 T.I.R.
- 6. DIMENSIONS TO BE MET BEFORE PLATING.
- 7. CHAMPER ALL THDS .45 DEGREES 8. THREADS PER H-2B
- 9. REMOVE FRAYED EDGES ON TEFLON.
- 10. REMOVE ALL BURRS.

		MATERIAL	SIZE	SPECIFICATION		PROCUREMENT	
				APPR.			
					ENG.		
					CHK.		
UNITED MICROWAVE PRODUCTS Inc.					DR.		
ONTED MICHOVAVET HODGOTO IIIC.					1390		
N JACK TO SMA PLUG ADAPTOR							