



PIDG FASTON Receptacles (Continued)


Ultra-Fast Plus Fully Insulated FASTON Receptacles

Material and Finish

Housing — Nylon
Terminal — Copper Alloy (see chart),
tin-plated

Color Code (Translucent)

Red — 22-18 AWG
Blue — 16-14 AWG



.110/.125 Series

Wire Range AWG [mm ²]	Ins. Dia. Max.	Mating Tab	Terminal Material	Part Numbers	
				Strip Form	Loose Piece
22-18 [0.3-0.9]	1.52-3.06 .060-.120	0.81 x 2.79/3.18 .032 x .110/.125	Brass	2-520979-2	—
		0.51 x 2.79/3.18 .020 x .110/.125	Brass	2-520932-2	—

.187 Series

Wire Range AWG [mm ²]	Ins. Dia. Max.	Mating Tab	Terminal Material	Part Numbers	
				Strip Form	Loose Piece
22-18 [0.3-0.9]	1.52-3.43 .060-.135	0.51 x 4.75 .020 x .187	Brass	2-520401-2	2-520409-2
		0.81 x 4.75 .032 x .187	Brass	3-520403-2	3-520411-2
16-14 [1.25-2.0]	2.29-4.06 .090-.160	0.51 x 4.75 .020 x .187	Brass	2-520402-2	2-520410-2
		0.81 x 4.75 .032 x .187	Brass	3-520404-2	3-520412-2

.250 Series

Wire Range AWG [mm ²]	Ins. Dia. Max.	Mating Tab	Terminal Material	Part Numbers	
				Strip Form	Loose Piece
22-18 [0.3-0.9]	1.52-3.43 .060-.135	0.81 x 6.35 .032 x .250	Brass	2-520405-2	2-520407-2
		0.81 x 6.35 .032 x .250	Brass	3-520406-2	3-520408-2

POWER

Terminals and Miscellaneous